Indentification and Position Estimation

by Nenny Anggraini

Submission date: 24-Jun-2019 09:28AM (UTC+0700) Submission ID: 1146483303 File name: IDENTI_1.PDF (408.49K) Word count: 2822 Character count: 15257 The 6th International Conference on Cyber and IT Service Management (CITSM 2018) Inta Parapat Hotel – Medin, August 7-9, 2018

Identification and Position Estimation Method with K-Nearest Neighbour and Home Occupants Activity Pattern

Alfatta Rezqa Winnersyah Department of Informatics, FST UIN Syarif Hidayatullah Jakarta, Indonesia arwinnersynh@gmail.com

Feri Fahrianto, M. Sc Department of Informatics, FST UIN Syarif Hidayatullah Jakarta, Indonesia feri, fahrianto@uinjkt.ac.id

E Abstract-As the number of home-based Internet of Things (IoT) applications such as home automation and monitoring of occupants behavior, indoor location information becomes a necessity. Previous research has been able to estimate indoor position using the fingerprinting method. In this paper, proposed a method that is able to estimate the indoor position of the occupants of the house by combining fingerprinting techniques with the home occupants activity pattern using K-Nearest Neighbour algorithms with Euclidean Distance. From the experimental results, this paper get results that the method that the proposed able to estimate with accuracy of up to 87.8% for accuracy below 2 meters with an average error of 9.82 meters.

Keyword—Indoor Positioning System, K-Neurest Neighbour, Activity Pattern

1. INTRODUCTION

Location is one of the important information in getting a variety of context-aware services. With mad home based applications of Internet of Things (IoT) such as home automation and behavioral monitoring of occupants, indoor location information becomes a necessity [4]. The current popular location determination method is the Global Positioning System (GPS), but GPS is not able to work well in an indoor environment [23]. GPS signals are blocked by building construction and do not work well to get locations in space [22].

Indoor position estimation methods can be done in various ways, such as using WiFi. Bluetooth, Ultra-Wide Band (UWB), and RFID. WiFi is one pretty good approach. Can be quite good because WiFi technology has been implemented in many buildings even in smartphones have embedded WiFi technology. In addition WiFi has a wider signal coverage compared to Bluetooth and RFID [4]. Nenny Anggraini, M.T Department of Informatics, FST UIN Syarif Hidayatullah Jakarta, Indonesia nenny anggraini@uinjkt.ac.id

WLANs can be used to determine a person's position in room by utilizing the value of Received Signal Strength Indication (IGSI) of multiple access points and with certain algorithms such as Support Vector Machines, Nearal Networks, Weighted K Nearest Neighbors, or Bayesian approach. Conducted a learning of the system at a predetermined location point to obtain learning data to be used in the next process [11].

Machine learning deals with how to build computer programs that automatically get better with experience

1] One approach in machine learning is classification. Classification is a job of valuing data objects to include them in a particular class of available classes. In the classification there are two main work done, namely (1) the development of the model as a prototype to be stored as memory and (2) the use of the model to perform the introdiction / classification / prediction on another data object to be known in the class where the data object is in the model which he has saved [12].

Based on the way of training, the classification algorithms can be divided into two types: eager learner and lazy learner. The algorithms included in the lazy learner category do little training (or none at all), only saving part or all of the training data, then using them in the prediction process. This resulted in a long prediction process because the model had to re-read all the training data in order to give the correct class label output on the test data provided. The advantages of such algorithms are the fast-paced training process. The classification plogorithms that fall into this category, among them, are K-Nearest Neighbor (K-NN). Fuzzy K-Nearest Neighbors (FK-NN), Linear Regression, and so on [12].

A common method used by calculating short-range or matching of data to be performed with existing learning data [4] [22] [23]. But from the closest distance is still often found the data made the results will be a wrong draw. In determining the position of the occupants of the house, one of the indicators associated with the position is the activity of the occupants of the house. Activities of occupants can easily be known because home activities belong to a certain pattern. For example, every morning everyone likes to get up and brush their teeth or breakfast [24]. The way home occupants can be used as one of the parameters in determining the position of the occupants of a house at a certain time. This pattern of activity will be used as a comparison so that the results of the WiFi form produce more accurate data.

11. RELATED WORKS

Previous research [4] has proposed an AP-Centered Indoor Positioning System compared to Mobile HH based. Fingerprinting technique used to combine MH-Based with AP-Centered, that is during the training process using MH but when the online phase only use sniffy program in AP. This becomes more efficient because no application is installed in MH during the online phase. This study also produced a maximum error distance of 4.5 meters. But because it is centered in the AP then have to configure the AP in order to install the sniffy program created. And the estimation data is not given to the detected person.

Next research [11] analyzed the measured RSS value on two university room divided into 21 point. Measurement using laptop with Netsurveyor software. In this study compared the measurement values of 4 APs with people inside, 4 APs without people inside, 2 APs with people inside, and 2 APs with no people inside. The results of this study indicate that RSS values will change as environmental conditions change. The challenge of the system is the construction of buildings, furniture, and the human body.

Other research [22] took a case study on a room at the university. Using fingerprinting techniques, researchers perform techniques by sending the RSS value of the user's android and processed on the server. Researchers used 6 APs that had been installed at a height of 1.2 meters from the floor. The K-Nearest Neighbors Algorithm with Euclidean Distance was used in this study. The area is divided into 20 points. The results of this study show that implementation is easy and more cost-effective. From experimental data it is known that displacement in the room area affects RSS values and decreases accuracy. Accuracy is obtained 42.5% -64.5% within 2 meters if there are people in the room. While the estimation results are returned to the user and displayed.

Next research [23] measured RSS with smartphone for 3 data sets. The first data set as training data while the second data set is the test data with the situation is placed and the third data set is test data with handheld state. The area is one floor of the university building which is divided into 6 dots. This research uses Density-Based Clustering Combined Localization Algorithm technique in making fingerprint. High enough accuracy of 97.28% to 99.85% for the second data set and 97.28% to 99.85% for the third data set. This shows the position of the smartphone when measurement greatly affects the accuracy of the results.

From some of these research results, it is known that positioning estimation technology is currently highly developed. The most effective method used in previous research is to use the fingerprinting technique, which takes some data for training data and then collects the data and is matched with the training data to get the calculation result. Research [23] is capable of obtaining high accuracy but with considerable spacing between dots because one floor of the university building is only divided into six dots. While research [22] produces applications that can determine the position of its users with a system that works on the server and use android as a sender of RSS value. The result, the accuracy has reached 42.75% to 64.5%. This is influenced by the number of people in the room. While in the study [4], a proposed non-application method for users using OpenWRT access point was developed by developing a sniffy program to monitor Probe Request from nearby devices. The result, able to predict the position with a maximum error distance of 4.5 meters, but the calculation results are not given to the user directly.

III. IDENTIFICATION AND POSITION ESTIMATION

A. Fingerprinting Technique

The fingerprinting technique in position estimation is

by recording the RSS value of multiple access points at a point. There are two main phases in fingerprinting technique, namely offline phase (training) and online positioning phase. The position of the reference point is determined by a distance of one or two meters. In the offline phase the RSS value is measured and stored into the database along with reference point information. Then in the positioning online phase, the RSS value is measured and compared to the RSS values available in the database to find the most suitable data.

B. K-Nearest Neighbour

The K-NN algorithm is an algorithm that classifies the proximity of the location (distance) of a data with other data. The value of K on K- NN means the number of nearest neighbors used as test data. One suitable distance can all ation method used in the K-NN algorithm is the euclidean distance. Euclidean distance is a straight distance between two points contained in the Euclidean space. For distance between points p and q having n dimensions, the distance is calculated by the formula:

n

$$d(p,q)=d(q,p)=\sqrt{\sum_{p \in I}}(q,p)^2$$
 (1)

C. Home Occupants Activity Pattern

Activities of occupants can easily be known because

home activities belong to a certain pattern. The fact is someone tends to do the same activity in the same environment. This show relation between environment and activities that a person undertakes in that environment. In estimating position of the occupants in the house, the activities of the occupants can be used as one indicator. From a known pattern of activity, the pattern will be used as a comparison for the results of a WiFi-hased method to produce more accurate data.

IV. EXPERIMENTAL STUDY

A. Determine Reference Point

In this paper, Inkscape software is used for designing home layout. The house that used has an area of 104.53 m2 with a length of 20.12 m and width of 6.42 m. Each reference point is located 1 m away. Access points are placed in 3 corners of the house which will be reachable by any reference point.




Fig. 1 Reference Points

B. Training Phase

Training data conducted in 5 days using the application with two times the data collection per day. Data is captured by capturing data every 5 seconds. Then the data is taken the average value. After that the data is sent to the web server to be stored into the database. From this training process obtained 720 data from 72 reference points that have been predetermined. Data is in the form of RSS value of 3 access points and reference point number.

Training Posici	Massing.	101	wi	140	Att	Maria
and the second se	0.000	1.00	0.00	114	22220000000	361
# Server:	1.00	1040	- 24	100	THE R. P. LEWIS CO., LANSING MICH.	
and the second se	28	104	1.06	-11	3096888	1.4
792.348.1.4	10.00	:94	1.05	040	NUMBER	100
	305	10	- 24	:41	10303408	1
End:)	584	-01	-1	34	MINHONAL	100
e. 1. (76) (1. (8))	- 31	- 44	- 74	- 84	2010/08/07/07	- 1
with :	34		1.04	- 44	10745-000000	11114
479	188	ास	1.04	- 44	102106-00101	
AND I THERE I MANY IN THE REAL PROPERTY.	75.	1140	- 10	1.46	227555904	10.0
Los Concentration Concentration	255		-31	124	MURINAL	- 20
PEL - many (BOER) on the relations	117	1000	1.04	1.04	1220-0308	1.0
1P1	14	104	- 61	100	WEIGHT MARKED	-14
TOT - HARP & RECEIPT - BRUIK DR 20130 AN AL		100	1.00	-81	HURSON	100
	188	- 14	.4	140	100000449	
1992	186	1940	1.000	100	2012/04/05 99:06:00	1

Fig. 2 Training Phase

C. Home Occupants Activity Pattern Observation

Observation is done by recording all the activities of occapants while in the house. The data recorded is when and where (based on the reference point) the activity is performed. Observation of occupant habits conducted in 7 days. From the results of this observation, occupants activities grouped into 4 time groups, morning (04:01-09:00), noon (09:01-15:00), evening (15:01-19:00), and night (19:01-04:00) to get the pattern in each time group. Once grouped, then calculated probability value in the existing time group and then store them in the database for use in the estimation process.

51	114			-	12	(mpd	140	-	-		The Distance of the local	1-10-2	-
÷	18	油		論	18		18		10	+	1 1 1		ा
ī.	- 7	T	1	T	12		18	十	Ŧ	푸	TI	1 12	1
÷	18	1	1	i.	1E		18		谱	18	1 4 1	1 12	1
Ē	18	1	E	1	E	1	18	1	T	17		1 12	1
Ŧ	1.00	1	E	1	E	1	IE	1	击	-	111	1 2	- 1
÷	100	平	100	-	12	100	100	÷	-E	÷.	1 3 1	1 11	
÷		4	4	-	周	1	12	1	平	平	王平日	1 11	1
1	1	Ť.	Ť	Ŧ	1	+	1	+	T	T	T		

D. Estimation Phase

In this paper, estimation process is centralized in server. Input data will be compared with training data as then compared with subject's activity pattern. Estimation phase conducted in 5 days. There are 18874 data that successfully estimated.

P Server:		And a second sec
10270014	- 644	Contractor Statistics (Statistics)
The resources		1.000.000.000.000.000.000.000.000
		I DESCRIPTION OF THE OWNER OWNER OF THE OWNER OWNER OF THE OWNER OWNE
- 441		1 0000000000000000000000000000000000000
		a initial second second at an an
		1 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
		CONTRACTOR AND A REAL PROPERTY AND A REAL PROP
		a deliverant parameters of the second
		a provident paragonic as in an
		* 2012 2 201 201 201 2 2 2 2
The second second	Contract of the local division of the local	

Fig. Estimation Phase

E. Testing Estimation Result

Estimation result tested with manual observation to 500 data samples that randomly chosen. Data samples compared with actual subject position.

10	BUILDING BI	- C	18	78	11	2 B	in the second	anar B	12
121212121212		121211212	******	+*******	********	*********	Constants and	1000	111111111
	1	or Redstreet	100	E					
	Instant I	12212	2	1	2				

Fig. 5 Testing Estimation Result

V. Discussion

From the results already described earlier, it is known that this method is able to prove that the pattern of home occupancy activities can be one important indicator in the estimation of positions in the house which can not be reached by Global Positioning System (GPS) technology. The result of estimation accuracy of the method that the proposed is also quite good because it is able to estimate with an average error distance only 0.82 meters.

Many things affect the estimation result using this method, as this method uses fingerprinting technique which use wireless signal from access point, where wireless signal is known to be very fluctuating to the condition of the surrounding environment so that if there is a significant change of environmental condition then the estimation result will not be good. In addition, the pattern of activities of the occupants of the house sometimes not always the same, there are times when occupants suddenly perform activities that have not been done before.

VI. CONCLUSION

Based on the discussion that has been described previously, can be concluded that the method that the proposed has been able to estimate the position of the occupants of the house with an average error below 1 meter. This method was built starting with training data collection, activity pattern observation, and final estimation. Combining fingerprinting techniques with home occupant activity patterns can improve the estimation accuracy. The fingerprinting technique using K-Nearest Neighbour algorithm with Euclidean Distance as a classification algorithm.

ACKNOWLEDGMENT

This work was supported in part by the Institute for Research and Community Services (LP2M) UIN Syarif Hidayatallah Jakarta.

REFERENCES

- Akkrys, K., Guvene, I., Aygur, R., Pala, N., & Kadri, A. (2015, March). IoT-based acceptancy monitoring techniques for energyefficient smart buildings. In Wireless Communications and Networking Conference Workshops (WCNCW), 2015 IEEE (pp. 58-63). IEEE.
- [2] Alpaydin, Ethem. Introduction to Machine Learning 2nd ed. 2010, MIT Press.
- [3] Bhartiya, Shekhar. 2016. 3 step roadmap for building machine learning systems, https://www.linkedin.com/pulse/3-step-road_map-buildingmachine-learning-systems-shekhar-bhartiya, diakses pada 30 Desember 2016.
- [4] Du, X., Wu, J., Yang, K., & Wang, L. (2016, December). An AP-Centred Indoor Positioning System Combining Fingerprint Technique. In Global Communications Conference (GLOBECOM), 2016 IEEE (pp. 1-6). IEEE.
- [5] Hasil Survei 2016 Asasiasi Penyelenggara Jaringan Internet Indonesia (APJII) https://www.apjic.or.id/survei2016/download/ FBY9pDwice3T04HALX71b/cqcfii/2zRG_diandath_04_Matet_2017_ 08/29 WIB

- [6] Kendoll, K.E & Kendoll, J.E. 2011. System Analysis and Design Eighth Edition. USA: Pearson Education, Inc.
- [7] Lamm Resmi PHP, PHP: What is PHP? http://php.net/manual/en/ intro-whatis.php diakses 14 Juni 2017 11:24 WIB
- [8] Laman Resmi PHP PHP: What can PHP do? http://php.net/ manual/arcintro-whatcando.php.14.Juni 2017 11:26 WIB
- [9] Mitchell, Tom M. 1997. Machine Learning. USA: McGraw-Hill Companies.
- [10] Nagroho, Adi. 2011. Perancangan dan Implementasi Sistem Basis Data. Yogyakarta : ANDI
- [11] Pirzula, N., Niyun, M. Y., Hussan, M. F., Subhan, F., & Sakidin, H. (2016, August). WLAN location fingerprinting technique for devicefree indoor localization system. In Computer and Information Sciences (ICCOINS), 2016. 3rd International Conference on (pp. 650-655). IEEE.
- [12] Prawryo, Eko. 2012. Data Mining : Konsep dar Aplikasi monggunakan MATLAB. Yogyakarta : ANDI
- [13] Press Release StatCounter 2017. Android overtakes Windows for first time. http://gs.statecounter.com/ press/android-overtakes-windows-forfirst-time.diakses 22 Moi 2017 22:31 WIB
- [14] Raharjo, Budi. 2011. Belajur Otofodak Membuat Database Menggunakas MySQL Bandung Informatika.
- [15] Raharjo, Budi dkk. 2012. Modul Penrograman WEB (ITTML, PHP, & MySQL). Bandung : Modula
- [16] Rizky, Socian, 2011. Konsep Diour Reknyasa Perangkat Lunak. Jakarta : PT. Prestasi Pustaka
- [17] Rosa A.S., M. Shalahuddin. 2014. Rekayasa Perangkat Lanak Terstruktur dan Beroriertasi Objek. Informatika. Bondung
- [18] Safiat, Nazruddin H. 2012. Android : Penrograman Aplikas Mobile Smartphone dan Tablet PC Berbasis Android. Bandung : Informatika
- [19] Sangaji, Etta Mamang & Sopish. 2010. Metodologi Penelitian Pendekatan Praktis dalam Penelitian.
- [20] Suprimito, Dodit & Agastina, Rini. 2012. Penirograman Aplikasi Android. Yogyakarta. MediaKom
- [21] Setanta, Edky. 2011. Basis Data dalam Tinjanan Konseptual. Yogyakana ANDI.
- [22] Thuong, N. T., Phong, H. T., Do, D. T., Van Hies, P., & Loc, D. T. (2016, January). Android application for WiFi based indeor position: System design and performance analysis. In Information Networking (ICOIN), 2016 International Conference on (pp. 416-419). IEEE.
- [23] Toh, C., & Lau, S. L. (2016, October). Indoor localisation using existing WiFi infrastructure — A case study at a university building. In Vietnal System & Multimedia (VSMM), 2016–22nd International Conference on (pp. 1-5). IEEE.
- [24] Yan, Y., Ricci, E., Rostamzadeh, N., & Sebe, N. (2014, October). It's all about habits: Exploiting multi-took clustering for activities of duily living analysis. In Image Processing (ICIP), 2014 IEEE International Conference on (pp. 1071-1075). IEEE.

Indentification and Position Estimation

ORIGIN	ALITY REPORT				
SIMILA	3 % ARITY INDEX	8% INTERNET SOURCES	11% PUBLICATIONS	0% STUDENT PAPE	ERS
PRIMAF	RY SOURCES				
1	www.ijct	journal.org			3%
2	Widya, A "Perform Protocol Internatio	ni Masruroh, Khai Andrew Fiade, Im- nance Evaluation RIP, OSPF, And onal Conference Management (CI ⁻	elda Ristanti J DMVPN Using EIGRP", 2018 on Cyber and	ulia. g Routing 3 6th	2%
3	iconquha				2%
4	AP-Cent Combini Global C	I, Jiuzhou Wu, Ku red Indoor Position ng Fingerprint Te communications (COM), 2016	oning System chnique", 2010	C C	1%
5		ni Masruroh, Andı nan, Amelia. "Per			1%

Fathul Iman, Amelia. "Performance evaluation routing protocol RIPv2, OSPF, EIGRP with

BGP", 2017 International Conference on Innovative and Creative Information Technology (ICITech), 2017

1%

1%

1%

Publication

6

Almas Shabrina, Feri Fahrianto, Nenny Anggraini. "Estimation system of occupant behavior against the use of electricity using Bayes method and decision tree algorithm", 2017 Second International Conference on Informatics and Computing (ICIC), 2017 Publication

- Sri Lestari Rahayu, Fujiati, Rofiqoh Dewi.
 "Educational Games as A learning media of Character Education by Using Multimedia Development Life Cycle (MDLC)", 2018 6th International Conference on Cyber and IT Service Management (CITSM), 2018 Publication
- 8

"CITSM 2018 TOC", 2018 6th International Conference on Cyber and IT Service Management (CITSM), 2018 Publication

9 Nasrullah Pirzada, M Yunus Nayan, M Fadzil Hassan, Fazli Subhan, Hamzah Sakidin. "WLAN location fingerprinting technique for device-free indoor localization system", 2016 3rd International Conference on Computer and

Information Sciences (ICCOINS), 2016

Publication

	~
1	
-	<u> </u>

www.scribd.com

<1%

11	Fauzan Burdi, Anif Hanifa Setianingrum, Nashrul Hakiem. "Application of the Naive Bayes Method to a Decision Support System to Provide Discounts (Case Study: PT. Bina Usaha Teknik)", 2016 6th International Conference on Information and Communication Technology for The Muslim World (ICT4M), 2016 Publication	< 1 %
12	csis.pace.edu Internet Source	<1%
13	widuri.raharja.info Internet Source	<1%
14	www.groundai.com	<1%
<mark>15</mark>	"Intelligent Systems Design and Applications", Springer Science and Business Media LLC, 2018 Publication	< 1 %

Exclude bibliography On

On